



CARRETILLAS ELEVADORAS

SGLIFT S.L.U

Polg Malpica-Alfinden C/ Noyal 59-50171

CIF B-99396392

Zaragoza -España

Tel/fax 876532223

E-mail: sglift@sglift.es



## TRANSPALETA ELECTRICA CBD15 -JH

~~1.900,00 €~~ **1.750,00 €** + IVA

**CAPACIDAD:** 1500kg

**MEDIDAS:** 680X1000

**BATERIA:** 24V-30Ah

**CARGADOR:** 24V-10Ah

**RODILLO:** Doble

**PROMOCION HASTA FINALIZAR STOCK**  
**unidades limitadas**

---

**SKU:** N / A

**Categorías:** [Transpaleta eléctrica](#)



## GALERÍA DE IMÁGENES

### Electric Pallet Truck

#### Introduction

The truck is simple and dexterous, with small turning radius and small weight. It is suitable for ultra-narrow channel operation.  
 The truck has compact and reliable structure. The oil pipeline and line are wrapped in the truck body which is safe and beautiful and convenient for user maintenance.  
 The truck adopts integrated handle design integrating key switch and electric meter which is simple and comfortable for operation.  
 Hand-held lithium battery makes battery changing easier and more convenient.  
 Standard configuration of emergency stop switch and emergency reverse device ensure truck safety.  
 The truck is loaded as soon as the handle is loosened or pressed to the bottom.  
 Electromagnetic braking and motor braking are used to ensure the safety of driving.


#### Options

As auxiliary wheels  
 Remote handle with pin code  
 Chargers 48V/1.5Ah, 48V/1.0Ah (for 2.0t)  
 In instead of the double-sided pallet rack  
 Electric lowering  
 Single front wheel  
 Manual release



### Electric Pallet Truck Specification

		HANGCHA GROUP CO., LTD.	
Characteristics	1.1 Model	08015-JP	08010-JP
	1.2 Power	0800W	0600W
Capacity	1.4 Operator type	Push-button	Push-button
	1.5 Load capacity / rated load	0.5t	0.5t
	1.6 Load center distance	600	600
	1.7 Load distance, center of drive axle to fork	344	344
Length	1.8 Wheelbase	1200	1245
	2.1 Service weight without battery	NA	137
Metric	3.1 Wheel type	PU	PU
	3.2 Drive wheel size	Ø160-70	Ø160-70
	3.3 Free wheel size	Ø80-40	Ø80-40
	3.4 Wheel center-to-center (C-C) distance	1245	1245
	3.5 Track size	1600x160	1600x160
	4.1 Lift height	1600	1600
	4.2 Height of fork in three position min./max	740/1100	740/1100
	4.3 Lowered height	85	85
	4.4 Drive shaft length	1000	1000
	4.5 Fork length	600	600
Dimension	4.6 Drive shaft length	550/605	550/605
	4.7 Fork dimension	1000/1000/1000	1000/1000/1000
	4.8 Fork access hole	550/605	550/605
	4.9 Ground clearance, center of wheelbase	35	35
	4.10 Fork width for pallet 1000 x 1200 mm (max)	1804	1804
	4.11 Fork width for pallet 800 x 1200 mm (max)	1854	1854
	4.12 The turning radius	1200	1200
	5.1 Travel speed, Latch condition	0.2/0.15	0.2/0.15
	5.2 Emptying speed, Latch condition	0.15	0.15
	Drive	5.3 Service brake	Electromagnetic
6.1 Drive motor rating at 50/60Hz		0.8/0.7	0.8
6.2 LIF motor rating at 53/55%		0.8	0.8
6.3 Battery according to DIN 45331/32/33/34/35/36/37/38		NA	48V
6.4 Battery voltage/nominal capacity		48V/10	48V/10
6.5 Battery weight (175%)		100	100
Data	7.1 Type of drive control	DC	DC
	7.2 Speed control at driver's seat	0/10	0/10
7.3 Steering type	Mechanical steering	Mechanical steering	





CARRETILLAS ELEVADORAS

SGLIFT S.L.U

Polg Malpica-Alfinden C/ Nogal 59-50171

CIF B-99396392

Zaragoza -España

Tel/fax 876532223

E-mail: sglift@sglift.es

## DESCRIPCIÓN DEL PRODUCTO

La transpaleta eléctrica está pensada para el transporte de mercancías dentro de naves, centros logísticos o fábricas, para la carga y descarga en espacios reducidos o para la preparación de pedidos a bajo nivel.

Nuestras maquinas son entregadas a los clientes luego de realizar una revisión técnica completa y de su restauración.

Ofrecemos opción de compra, alquiler o renting.

Opción de pago:

- Transferencia bancaria

- Financiación