



CARRETILLAS ELEVADORAS

SGLIFT S.L.U

Polg Malpica-Alfinden C/ Noyal 59-50171

CIF B-99396392

Zaragoza -España

Tel/fax 876532223

E-mail: sglift@sglift.es



## TRANSPALETA ELECTRICA CBD15 -JH

~~1.900,00 €~~ **1.750,00 €** + IVA

**CAPACIDAD:** 1500kg

**MEDIDAS:** 680X1000

**BATERIA:** 24V-30Ah

**CARGADOR:** 24V-10Ah

**RODILLO:** Doble

**PROMOCION HASTA FINALIZAR STOCK**  
**unidades limitadas**

---

**SKU:** N / A

**Categorías:** [Transpaleta eléctrica](#)



## GALERÍA DE IMÁGENES

### Electric Pallet Truck

#### Introduction

- / The truck is simple and dexterous, with small turning radius and small weight. It is suitable for ultra-narrow channel operation.
- / The truck has compact and reliable structure. The oil pipeline and line are wrapped in the truck body which is safe and beautiful and convenient for user maintenance.
- / The truck adopts integrated handle design integrating key switch and electric meter which is simple and comfortable for operation.
- / Hand-held lithium battery makes battery changing easier and more convenient.
- / Standard configuration of emergency stop switch and emergency reverse device ensure truck safety.
- / The truck is assembled with power-off braking function.
- / The truck is locked as soon as the handle is loosened or pressed to the bottom.
- / Electromagnetic braking and motor braking are used to ensure the safety of driving.


#### Options

- / Auxiliary wheels
- / Remote handle with pin code
- / Chargers 48V/1.5Ah, 48V/1.0Ah (for 2.0t)
- / In instead of the double-sided pallet rack
- / Electric lowering
- / Single front wheel
- / Manual release



#### Electric Pallet Truck Specification

		HANGCHA GROUP CO., LTD.	
Characteristics	1.1 Model	08015-JP	08010-JP
	1.2 Power	08015	08010
Capacity	1.4 Operator type	Push-button	Push-button
	1.5 Load capacity / rated load	0.5t	0.5t
	1.6 Load center distance	600	600
	1.7 Load distance, center of drive axle to fork	344	344
Length	1.8 Wheelbase	1203	1245
	2.1 Service weight without battery	NA	137
Metric	3.1 Wheel type	PS	PS
	3.2 Drive wheel size	Ø160-70	Ø160-70
	3.3 Fork wheel size	Ø80-60	Ø80-60
	3.4 Wheel center-to-center (C-C) distance	1245	1245
	3.5 Track size	1600x160	1600x160
	4.1 Lift height	1000	1000
	4.2 Height of fork in three position min./max	740/1100	740/1100
	4.3 Lowered height	85	85
	4.4 Drive shaft length	1003	1003
	Dimension	4.5 Fork dimensions	Ø60
4.6 Drive shaft length		Ø60	Ø60
4.7 Fork dimensions		550x60	550x60
4.8 Fork dimensions		1000x160	1000x160
4.9 Fork dimensions		550x60	550x60
4.10 Fork dimensions		1000x160	1000x160
4.11 Fork dimensions		1000x160	1000x160
4.12 Fork dimensions		1000x160	1000x160
4.13 Fork dimensions		1000x160	1000x160
4.14 Fork dimensions		1000x160	1000x160
Drive	5.1 Travel speed, Load condition	0.8m/s	0.8m/s
	5.2 Emptying speed, Load condition	0.5	0.5
	5.3 Service brake	Electromagnetic	Electromagnetic
	5.4 Drive motor rating at 50/60Hz	0.6	0.6
	5.5 Drive motor rating at 50/60Hz	0.6	0.6
	5.6 Battery according to DIN 45331/32/33/34/35/36/37	48V	48V
	5.7 Battery voltage	48V	48V
	5.8 Battery voltage	48V	48V
	5.9 Battery weight (1.75h)	11.5	11.5
	5.10 Battery weight (1.75h)	11.5	11.5
Data	7.1 Type of drive control	DC	DC
	7.2 Speed control at driver's seat	0.5t	0.5t
7.3 Braking type	Electromagnetic braking	Electromagnetic braking	





CARRETILLAS ELEVADORAS

SGLIFT S.L.U

Polg Malpica-Alfinden C/ Nogal 59-50171

CIF B-99396392

Zaragoza -España

Tel/fax 876532223

E-mail: sglift@sglift.es

## **DESCRIPCIÓN DEL PRODUCTO**

La transpaleta eléctrica está pensada para el transporte de mercancías dentro de naves, centros logísticos o fábricas, para la carga y descarga en espacios reducidos o para la preparación de pedidos a bajo nivel.

Nuestras maquinas son entregadas a los clientes luego de realizar una revisión técnica completa y de su restauración.

Ofrecemos opción de compra, alquiler o renting.

Opción de pago:

- Transferencia bancaria

- Financiación