CARRETILLAS ELEVADORAS
SGLIFT S.L.U
Polg Malpica-Alfinden C/ Nogal 59-50171
CIF B-99396392
Zaragoza -España
Tel/fax 876532223
E-mail: sglift@sglift.es

TRANSPALETA ELECTRICA CBD15 -JH

~~**1.900,00 €**~~ **1.750,00 €** **+ IVA**

CAPACIDAD: 1500kg

MEDIDAS: 680X1000

BATERIA: 24V-30Ah

CARGADOR: 24V-10Ah

RODILLO: Doble

PROMOCION HASTA FINALIZAR STOCK
unidades limitadas

SKU: N / A
Categorías: Transpaleta eléctrica

CARRETILLAS ELEVADORAS
SGLIFT S.L.U
Polg Malpica-Alfinden C/ Nogal 59-50171
CIF B-99396392
Zaragoza -España
Tel/fax 876532223
E-mail: sglift@sglift.es

GALERÍA DE IMÁGENES

Electric Pallet Truck Specification

				HANGCHA GROUP CO.,LTD.					
Characteristics	1.1	Manufacturer		HANGCHA GROUP CO.,LTD.					
	1.2	Model		CBD15-JH			CBD20-JH		
	1.3	Power		Electric			Electric		
	1.4	Operator type		Pedestrian			Pedestrian		
	1.5	Load capacity / Rated load	Q (t)	1.5			2.0		
	1.6	Load centre distance	c (mm)	600			600		
	1.7	Load distance, centre of drive axle to fork	x (mm)	944			944		
	1.8	Wheelbase	y (mm)	1243			1243		
Weights	2.1	Service weight without battery	kg	137			146		
Wheels, Tyres	3.1	Wheels type		PU			PU		
	3.2	Drive wheel size	Ø×w(mm)	Ø210×70			Ø210×70		
	3.3	Fork wheels size	Ø×w(mm)	Ø80×60			Ø80×60		
	3.4	Wheels, number front/rear (x = driven)		1x/4			1x/4		
	3.5	Tread, rear	bx1 (mm)	400/535			400/535		
Dimensions	4.1	Lift height	h3 (mm)	200			200		
	4.2	Height of tiller in drive position min. / max	h14 (mm)	740/1160			740/1160		
	4.3	Lowered height	h13 (mm)	85			85		
	4.4	Overall length	l1 (mm)	1603			1603		
	4.5	Length to face of forks	l2 (mm)	453			453		
	4.6	Overall width	b1/ b2 (mm)	550/685			550/685		
	4.7	Fork dimensions	s/e/l (mm)	50/150/1150			50/150/1150		
	4.8	Width across forks	b4 (mm)	550/685			550/685		
	4.9	Ground clearance, centre of wheelbase	m2 (mm)	35			35		
	4.10	Aisle width for pallet 1000 x 1200 crossways	Ast (mm)	1804			1804		
	4.11	Aisle width for pallet 800 x 1200 lengthways	Ast (mm)	1854			1854		
	4.12	Min.turning radius	Wa (mm)	1398			1398		
Performance Data	5.1	Travel speed, laden/unladen	(km/h)	4.2/4.5			4.2/4.5		
	5.2	Gradeability, laden/ unladen	(%)	5/10			5/10		
	5.3	Service brake		Electromagnetic			Electromagnetic		
Drive	6.1	Drive motor rating S2 60min	(kW)	0.75			1.0		
	6.2	Lift motor rating at S3 15%	(kW)	0.8			0.8		
	6.3	Battery according to DIN 43531/35/36 A,B,C,no		no			no		
	6.4	Battery voltage/rated capacity	(V/Ah)	24/20	24/30	24/40	48/15	48/20	
	6.5	Battery weight (± 5%)	(kg)	5.5	7	8.2	7	8.2	
Others	7.1	Type of drive control		DC			DC		
	7.2	Sound level at driver's ear	(dB(A))	≤70			≤70		
	7.3	Steering type		Mechanical steering			Mechanical steering		



CARRETILLAS ELEVADORAS
SGLIFT S.L.U
Polg Malpica-Alfinden C/ Nogal 59-50171
CIF B-99396392
Zaragoza -España
Tel/fax 876532223
E-mail: sglift@sglift.es

DESCRIPCIÓN DEL PRODUCTO

La transpaleta eléctrica está pensada para el transporte de mercancías dentro de naves, centros logísticos o fábricas, para la carga y descarga en espacios reducidos o para la preparación de pedidos a bajo nivel.

Nuestras maquinas son entregadas a los clientes luego de realizar una revisión técnica completa y de su restauración.

Ofrecemos opción de compra, alquiler o renting.

Opción de pago:

– Transferencia bancaria

– Financiación