



CARRETILLAS ELEVADORAS

SGLIFT S.L.U

Polg Malpica-Alfinden C/ Noyal 59-50171

CIF B-99396392

Zaragoza -España

Tel/fax 876532223

E-mail: sglift@sglift.es



TRANSPALETA ELECTRICA CBD15 -JH

~~1.900,00 €~~ 1.750,00 € + IVA

CAPACIDAD: 1500kg

MEDIDAS: 680X1000

BATERIA: 24V-30Ah

CARGADOR: 24V-10Ah

RODILLO: Doble

PROMOCION HASTA FINALIZAR STOCK
unidades limitadas

SKU: N / A

Categorías: [Transpaleta eléctrica](#)



CARRETIILLAS ELEVADORAS

SGLIFT S.L.U

Polg Malpica-Alfinden C/ Noyal 59-50171

CIF B-99396392

Zaragoza -España

Tel/fax 876532223

E-mail: sglift@sglift.es

GALERÍA DE IMÁGENES

Electric Pallet Truck

Introduction

- / The truck is simple and dexterous, with small turning radius and small weight. It is suitable for ultra-narrow channel operation.
- / The truck has compact and reliable structure. The oil pipeline and line are wrapped in the truck body which is safe and beautiful and convenient for user maintenance.
- / The truck adopts integrated handle design integrating key switch and electric meter which is simple and comfortable for operation.
- / Hand-held lithium battery makes battery changing easier and more convenient.
- / Standard configuration of emergency stop switch and emergency reverse device ensure truck safety.
- / The truck is assembled with power-off braking function.
- / The truck is locked as soon as the handle is loosened or pressed to the bottom.
- / Electromagnetic braking and motor braking are used to ensure the safety of driving.


Options

- / Auxiliary wheels
- / Remote handle with pin code
- / Chargers 48V/1.5Ah, 48V/1.0Ah (for 2.0t)
- / In instead of the double-sided pallet rack
- / Electric lowering
- / Single front wheel
- / Manual release



Electric Pallet Truck Specification

		HANGCHA GROUP CO., LTD.	
Characteristics	1.1 Model	08015-JH	08010-JH
	1.2 Power	08015	08010
	1.4 Operator type	Push-button	Push-button
	1.5 Load capacity / rated load	1.5t	2.0t
Length	1.6 Load entry distance	6100	6000
	1.7 Load distance, center of drive axle to fork	3464	3464
	1.8 Wheelbase	1210	1245
	2.1 Service weight without battery	NA	137
Metric	3.1 Wheel type	PS	PS
	3.2 Drive wheel size	Ø160-70	Ø160-70
	3.3 Fork wheel size	Ø80-60	Ø80-60
	3.4 Wheel center-to-center (C-C) distance	1210	1245
	3.5 Track size	1600/155	1600/155
	4.1 Lift height	760	760
	4.2 Height of fork in three position (min./max)	740/1100	740/1100
	4.3 Lowered height	65	65
	4.4 Drive shaft length	1003	1003
	4.5 Fork dimensions	Ø67	Ø67
Dimension	4.6 Drive shaft length	550/605	550/605
	4.7 Fork dimensions	1003/1003	1003/1003
	4.8 Fork access hole	550/605	550/605
	4.9 Ground clearance, center of wheelbase	35	35
	4.10 Fork width for pallet 1100 x 1100 mm (max)	1894	1894
	4.11 Fork width for pallet 800 x 1200 mm (max)	1894	1894
	4.12 Max. turning radius	1208	1208
	5.1 Travel speed, Latched condition	0.20/0.15	0.20/0.15
	5.2 Escalating speed condition	0.3	0.3
	5.3 Service brake	Electromagnetic	Electromagnetic
Drive	6.1 Drive motor rating at 50/60Hz	0.6/0.5	0.6
	6.2 LIF motor rating at 5.5/5.5%	0.8	0.8
	6.3 Battery according to DIN 45331/32/33/34/35/36/37	NA	48V
	6.4 Battery voltage/nominal capacity	48V/10	48V/10
	6.5 Battery weight (1.5%)	100	100
	7.1 Type of drive control	EC	EC
	7.2 Speed control at driver's seat	0.70	0.70
7.3 Steering type	Mechanical steering	Mechanical steering	





CARRETILLAS ELEVADORAS

SGLIFT S.L.U

Polg Malpica-Alfinden C/ Nogal 59-50171

CIF B-99396392

Zaragoza -España

Tel/fax 876532223

E-mail: sglift@sglift.es

DESCRIPCIÓN DEL PRODUCTO

La transpaleta eléctrica está pensada para el transporte de mercancías dentro de naves, centros logísticos o fábricas, para la carga y descarga en espacios reducidos o para la preparación de pedidos a bajo nivel.

Nuestras maquinas son entregadas a los clientes luego de realizar una revisión técnica completa y de su restauración.

Ofrecemos opción de compra, alquiler o renting.

Opción de pago:

- Transferencia bancaria

- Financiación